



WET PROCESSING SYSTEMS

Precision Dyeing Equipment



U.S.A.

ISO 9001:2015 Certified
(Quality Management System)

All Braun Products are Proudly
Manufactured in the U.S.A.

gabraun.com

WET PROCESSING SYSTEMS



Braun Dye-Extractors provide the highest degree of precision, speed, economy, and confidence.

Braun Dye-Extractors are available in multi-pocket Top/Side Loader (TSL) models. Each provides the highest degree of precision, speed, economy, and confidence available on the market today. Braun Dye-Extractors also offer savings on time, water, energy, floor space, and labor.

BRAUN DYE-EXTRACTOR FEATURES

INTELLIGENCE

Industry leading controls allow you to program all dyeing processes – cycle times, cylinder speeds, liquor ratios, water temp, dye and chemical injection, controlled temperature rate of rise and cool-down and extraction, and they are completely self-diagnostic.

ECONOMY

Low liquor dyeing saves water, chemicals, and energy costs.

INNOVATION

Braun's Patented Center Shaft Injection system (CSI) allows dye liquor to be circulated from the heat exchanger through the center shaft of the cylinder as well as through normal injection ports, thereby achieving penetration of the goods from two directions simultaneously at the lowest possible cylinder speeds. (The CSI feature is available on all Braun Top Side Loading Dye-Extractors.)

EASE

Liquor ratio controls allow you to program and maintain specific ratio of mass of water to mass of goods – to ensure consistency of dyeing. Once a procedure is established, simply enter the weight of goods as basis for water injection calculation.

EFFECTIVENESS

Dye liquor is recirculated through the system at a rate of 100 and 225 gallons per minute on 200-pound capacity machines, 450 gallons per minute on 400 and 600-pound capacity machines, and 700 Gpm to ensure level dyeing and successful penetration at low cylinder speeds. Optionally available on the Top/Side Loading Dye-Extractor is the Center Shaft Injection which recirculates dye liquor directly through the center shaft of the cylinder for dyeing at extremely low cylinder speeds. During recirculation, the filtration system removes lint and contaminants from the dye bath.

The PenSurge feature enhances dye penetration and the distribution of goods by increasing and decreasing cylinder speed at programmable intervals during the dyeing cycle.

GENTLENESS

Braun Variable Speed Drive (VSD) provides a spectrum of cylinder speeds to ensure adequate dye penetration while maintaining gentle agitation. In addition, Braun cylinders are polished to a pick-free state.

TEMPERATURE CONTROL

The Braun External Heat Exchanger provides a precise rate of rise from 1° to 10° F per minute, plus maintenance of dye temperatures and controlled rate of both direct and indirect cool-down.

SMOOTH LOAD & UNLOAD

All models are designed for unobstructed, fast gravity-assisted loading and unloading – easily accommodating sling load systems and carts or conveyors for unloading.

CAPACITY

Choose from 200-, 400-, 600- and 800-pound load sizes.

SIMPLICITY

Braun design allows for ease of in-plant maintenance and maximizes dependability.

STABILITY

Simple and effective Braun Neutron Suspension isolates vibration allowing for high speed extraction – two-speed extraction standard on all models. High speed extraction reduces drying time and saves energy.

ERGONOMICS

All Braun wet processing machines feature a convenient door height. The Top/Side Loading machines have cylinder configurations which use gravity to ease loading and unloading.

STRENGTH

Wetted parts are 316L stainless steel. All Braun Dye-Extractors come standard with five add-tanks. Optional tanks are available, including a 60-gallon model.



A Line of Wet Processing Equipment That Continues the Tradition of Excellence You've Come to Expect.

SPECIFICATIONS

For detailed equipment specifications please consult with your Braun Regional Sales Manager or contact us by email at equipmentspecifications@gabraun.com



ISO 9001:2015 CERTIFIED
(Quality Management System)

G.A. Braun, Inc.
79 General Irwin Boulevard
N. Syracuse, NY 13212

Mail to:
P.O. Box 3029
Syracuse, NY 13220-3029

Phone
1-800-432-7286

Fax
(315) 475-4130

Parts Help Desk
1-800-432-7286 X 1

Service Help Desk
1-800-432-7286 X 2



U.S.A.

All Braun Products are Proudly
Manufactured in the U.S.A.